



FLUSSOL ANTIFREEZE GW11-40°C

Antifreeze Ready mix for Motor Vehicles

Description

FLUSSOL Antifreeze GW 11 (-40°C) is a ready water-diluted antifreeze based on ethylenglycole. It is free of amines, nitrites and phosphates. The special inhibitor-package protects outstandingly the engine and the cooling circuit against frost, rust and excessive heat. It is also applicable for light metal motors.

FLUSSOL Antifreeze GW 11 (-40°C) is pre-diluted by demineralized water. It may be used undiluted or be further diluted by normal tap water. The minimum concentration, in order to assure a sufficient corrosion protection, should not go below 50%. This is especially regarded at summer operation.

It is recommended to change the antifreeze at least after 5 years operating time.

If the engine constructor specifies the use of a product free of silicate, the respective operation instruction has to be regarded (VW, Audi, Seat, Skoda, Ford, GM/Opel from 1997).

Specifications / Recommendations

MB 325.0 & 325.2	Opel GME L301	Ford ESD-M97B94-A
BMW GS 94000	Saab 6901 599	MTU MTL 5048
MAN 324 NF	Lada TTM VAZ 1.97.717-97	
Cummins 85T8		
Volvo 128		
VW / Audi / Seat / Skoda / Porsche TL 774-C (G11)		

FLUSSOL Antifreeze GW 11 (-40°C)	Unit	VALUE
Density at 20°C	kg/m ³	1084
Colour		Blue
Pour Point	°C	-40
Flash Point	°C	>100
pH		8,4
Boiling Point	°C	>145

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further information to be available by MSDS.