



FLUSSOL GEAR BOX 4 SMT SAE 75W-80

Fully-Synthetic Standard Transmission Oil

Description

FLUSSOL GEAR BOX 4 SMT 75W-80 is made from high quality synthetic base oil and a high quality viscosity modifier. In combination with a modern additive-package there is achieved a performance level which has to be described as follows:

- excellent high pressure- and wear protection properties
- good to very good properties in corrosion- and rust protection
- low foaming tendency and excellent aging stability
- high viscosity index and low pour point care for easy gear changing
- even at high temperatures
- reduced oil consumption and extended oil drain intervals.

FLUSSOL GEAR BOX 4 SMT 75W-80 is used for the lubrication of synchronized and non-synchronized standard transmissions. Especially it is recommended for commercial vehicles, which are furnished with ZF manual transmissions, and it also is suitable for mechanic gears and steering's with re-/intarders.

Specifications / Recommendations

API GL-4

ZF TE-ML 01L, 02L, 08, 13, 16K, 24A

IVECO

MAN 341 Type Z-4

Volvo 97307

Eaton Extended Drain (300,000 km)

DAF

RENAULT (IN ACCORDANCE WITH RENAULT NOTE
TECHNIQUE B0032/2 ANNEX 3)

FLUSSOL GEAR BOX 4 SMT 75W-80	Unit	VALUE	Method
Density at 15°C		854	DIN 51 757
Viscosity at 40°C	kg/m ³	50,4	DIN 51 562
Viscosity at 100°C	mm ² /s	8,7	DIN 51 562
Viscosity Index		151	DIN ISO 2909
Pour point	°C	-39	DIN ISO 3016
Flash point	°C	228	DIN ISO 2592

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further information to be available by MSDS.