

FLUSSOL UHPD SAE 10W-40 HIGH PERFORMANCE OIL FOR EURO-4 and EURO-5 COMMERCIAL CAR ENGINES

Description

FLUSSOL UHPD SAE 10W-40 is a high-performance engine oil, which is made from base oils of the most modern synthesis technology. It is suitable for each kind of diesel engines in commercial cars, especially for EURO 4- and - 5- motors (EURO 4 &-5 does only limited apply to MAN and DAF). **B**enefits

FLUSSOL UHPD SAE 10W-40 assures top performance in many quality criterions:

- Easy low-wear cold-start by good fluidity, even at low temperatures.
- Excellent aging and corrosion protection.
- Exceeding wear protection and cleaning power.
- Allows the most extended oil drain intervals which car producers recommend.
- Outstanding thermal oxidative stability and low evaporation tendency.
- High performance additives and the synthetic base care for unexcelled performance.

Specifications / Recommendation

ACEA E4- / E7	Scania LDF-2	MB 228.5	
API CI-4 / SL	Caterpillar ECF 1-a	MAN M 3277	
Renault RXD	VOLVO VDS-3	MAN M 3377	
Deutz DQC III-10	Mack EO-N		
МТU Тур 3	Renault VI RLD-2		
Cummins CES 20076, 20077, 20078			

Values

FLUSSOL UHPD SAE 10W-40	Unit	Value	Method
Density at 15°C	kg/m³	868	DIN 51 757
Viscosity at 40°C	mm²/s	103,0	DIN 51 562
Viscosity at 100°C	mm²/s	14,6	DIN 51 562
Viscosity Index		145	DIN ISO 2909
CCS at -25°C	mPa.s	6400	DIN 51 377
Pourpoint	°C	-36	DIN ISO 3016
Flashpoint	°C	224	DIN ISO 2592
TBN	mg KOH/g	12,5	DIN ISO 3771

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further information to be available by MSDS.